

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT WE, Takayuki Watanabe, a citizen of Japan residing at Yamanashi, Japan, Tsutomu Michitsuta, a citizen of Japan residing at Yamanashi, Japan, Taro Hasegawa, a citizen of Japan residing at Yamanashi, Japan and Takuya Fujii, a citizen of Japan residing at Yamanashi, Japan have invented certain new and useful improvements in

PROCESS OF MANUFACTURING A SEMICONDUCTOR DEVICE

of which the following is a specification : -

TITLE OF THE INVENTION

**PROCESS OF MANUFACTURING A SEMICONDUCTOR
DEVICE**

5 BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention generally relates to a compound semiconductor device and particularly relates to a process of manufacturing an optical semiconductor device used for optical communications and optical information processing.

A compound semiconductor has a band structure of a direct transition type that interacts with light and thus an optical semiconductor device utilizing compound semiconductor is widely used in the fields of optical communications and optical information processing. An InP material system's semiconductor device, particularly a laser diode, is important since it produces optical signals having a wavelength of 1.3 or 1.55 μm band which may be transmitted in an optical fiber.

2. Description of the Related Art

In order to improve laser oscillation efficiency for such a laser diode, it is necessary to provide a current blocking structure for confining injected carriers within a limited region along an axial direction. Further, since laser oscillation is produced by induced emission, light should also be efficiently confined within the region where the carriers are confined. For a laser diode of an InP material system, a horizontal light-confinement effect is achieved by adjusting a difference of refractive indices of the InGaAsP core for guiding the light and an InP buried layer.

Figs. 1A to 1D are diagrams showing various steps of a manufacturing process of a laser diode 10 having a buried-hetero (BH) structure which

serves as an electric current and light confinement structure.

Referring to Fig. 1A, a multi-quantum well layer 12 is formed over an n-type InP (n-InP) substrate 11. The multi-quantum well layer 12 includes repeatedly stacked InGaAsP layers. Further, a p-type InP (p-InP) cladding layer 13 and a p-type InGaAs (p-InGaAs) contact layer 14 are, in turn, formed on the multi-quantum well layer 12.

Then, in a step shown in Fig. 1B, a SiO₂ film 15 serving as an etching protection layer is formed on the contact layer 14. Then, dry etching is performed on such a structure to form active layer mesa-stripes. In the illustrated example, the mesa-stripes extend in the <011> direction.

In a step shown in Fig. 1C, a metal organic vapor phase epitaxy (MOVPE) is performed using the SiO₂ film 15 as a selective growth mask, such that crystals grow on both sides of the mesa strips to produce Fe-doped high-resistance InP buried layers 16A and 16B. During a regrowth step of such InP buried layers 16A and 16B, the (111) B surface develops which is a growth-stop surface. As a result, the buried layer builds up at the edge of the mask and gives a growth configuration that is raised as shown by reference numerals 16a and 16b.

Finally, in a step shown in Fig. 1D, the SiO₂ film 15 is removed, a p-side electrode 17 is formed on the contact layer 14 and an n-side electrode 18 is formed on a lower surface of the substrate 11.

As has been described above, when a buried growth process of the InP layers 16A and 16B is performed using the SiO₂ film 15 as a selective growth mask, the InP layers 16A and 16B inevitably rises at the regions 16a and 16b which correspond to the edges of the SiO₂ film 15. This is due to the

fact that the crystals do not grow on the SiO_2 film 15 and thus the concentration of the material locally increases on the SiO_2 film 15. This causes an excessive supply of the material to the surface of the InP layer 16A or 16B grown on both sides of the mesa-region. For the step shown in Fig. 1C, when the height of the mesa-stripe is about $1.5 \mu\text{m}$, the InP layers 16A, 16B will rise about $0.7 \mu\text{m}$ at the regions 16a, 16b at the edge of the mask.

As has been described above, in the step shown in Fig. 1D, the p-side electrode 17 is formed on such a stepped surface. When a Ti layer, a Pt layer and an Au layer are sputtered in turn to form the p-side electrode 17, the Ti layer and the Pt layer each has a thickness of only about $0.1 \mu\text{m}$. Therefore, as shown in Fig. 2, a break or discontinuity of the electrode layer may occur at uneven parts 17a due to the stepped configuration of the underlying structure. Such a break of the electrode causes an uneven electric current flow and thus gives rise to electric degradation of the device.

SUMMARY OF THE INVENTION

Accordingly, it is a general object of the present invention to provide a novel and useful process of manufacturing a semiconductor device which can solve the problems described above.

It is another and more specific object of the present invention to provide a process of manufacturing a semiconductor device in which, after forming a stepped structure of InP in a region adjacent to a mesa structure including a III-V group compound semiconductor layer by a regrowth process of an InP layer using a selective growth mask, the stepped structure is planarized by a simple wet-etching process to provide a planarized surface

substantially flush with the surface of the III-V compound semiconductor layer.

According to the present invention, a process of manufacturing a semiconductor device includes the steps of:

a) forming a stacked structure of a first III-V compound semiconductor layer containing In and having a composition different from InP and a second III-V compound semiconductor layer containing In, the second III-V compound semiconductor layer being formed over the first III-V compound semiconductor layer;

b) growing an InP layer at regions adjacent the stacked structure to form a stepped structure of InP; and

c) wet-etching the stepped structure and the second III-V compound semiconductor layer using an etchant containing hydrochloric acid and acetic acid to remove at least the second III-V compound semiconductor layer.

For a selective growth process of forming an InP buried layer at positions adjacent to a mesa-structure including III-V compound semiconductor layer containing In and having a composition different from InP using a selective growth mask, an etching rate adjusting layer of III-V compound semiconductor is formed on the above-mentioned compound semiconductor layer and then a wet-etching process is performed on the InP buried layer and the etching rate adjusting layer using an etchant containing hydrochloric acid and acetic acid. Accordingly, with such a process of manufacturing a semiconductor device, the stepped parts produced during the selective growth step of the InP buried layer can be eliminated and a planarized surface can be obtained which is flush with the upper surface of the above-mentioned compound semiconductor layer.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Figs. 1A to 1C are diagrams showing various steps of a manufacturing process of a laser diode having a buried hetero structure of the related art.

Fig. 2 is a diagram showing a problematic aspect of the process of Fig. 1.

10 Fig. 3 is a graph for explaining the principle of the present invention.

Fig. 4 is another graph for explaining the principle of the present invention.

Fig. 5 is still another graph for explaining the principle of the present invention.

15 Fig. 6 is yet another graph for explaining the principle of the present invention.

20 Figs. 7A to 7D are diagrams showing various steps of a first basic type of the process of manufacturing the semiconductor device of the present invention.

Figs. 8A to 8D are diagrams showing various steps of a second basic type of the process of manufacturing the semiconductor device of the present invention.

25 Figs. 9A to 9C are diagrams showing various steps of a third basic type of the process of manufacturing the semiconductor device of the present invention.

30 Figs. 10A to 10D are diagrams showing various steps of a fourth basic type of the process of manufacturing the semiconductor device of the present invention.

35 Figs. 11A to 11C are diagrams showing various steps of a manufacturing process of a first embodiment of the present invention.

Figs. 12D to 12G are diagrams showing various steps following the steps shown in Fig. 11C.

Figs. 13A to 13C are diagrams showing various steps of a manufacturing process of a second embodiment of the present invention.

5 Figs. 14D to 14F are diagrams showing various steps following the steps shown in Fig. 13C.

Figs. 15A to 15C are diagrams showing various steps of a manufacturing process of a third embodiment of the present invention.

10 Figs. 16D to 16F are diagrams showing various steps following the steps shown in Fig. 15C.

Figs. 17A to 17C are diagrams showing various steps of a manufacturing process of a fourth embodiment of the present invention.

15 Figs. 18D to 18E are diagrams showing various steps following the steps shown in Fig. 17C.

Figs. 19A to 19C are diagrams showing various steps of a manufacturing process of a fifth embodiment of the present invention.

20 Figs. 20D to 20E are diagrams showing various steps following the steps shown in Fig. 19C.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

25 In the following, principles and embodiments of the present invention will be described with reference to the accompanying drawings.

Referring to Figs. 3 to 6, principles of the present invention will be described. Fig. 3 is a graph showing an etching amount toward the $\langle 100 \rangle$, $\langle 0-11 \rangle$ and $\langle 011 \rangle$ directions with respect to etching time for a basic experiment of the present invention in which an etching process is performed on a stepped InP layer using a mixture of hydrochloric acid, acetic acid and water mixed at a ratio of
35 1:5:1.

Referring to Fig. 3, it can be seen that the etching rates to the $\langle 100 \rangle$ and $\langle 011 \rangle$ directions

are about 0.05 to 0.1 $\mu\text{m}/\text{min}$, where as the etching rate to the $\langle 0-11 \rangle$ direction is about 15 $\mu\text{m}/\text{min}$, which is more than a hundred times greater than the etching rates to the $\langle 100 \rangle$ and $\langle 011 \rangle$ directions.

5 Therefore, when the stepped configuration is etched using the above-mentioned mixture, the stepped part to the $\langle 0-11 \rangle$ direction recedes at a high rate. Accordingly, only the (100) and (011) surfaces and equivalent (0-1-1) surface remains as development
10 surfaces and other surfaces will disappear. That is to say, it can be seen that by a wet-etching process using the above-mentioned etchant, only the (100), (011) or (0-1-1) surface will appear as a planarized surface on the InP layer.

15 When the ratio of the components in the etchant is altered, absolute etching rates will vary and relative etching rates with respect to each surface orientation will also vary.

Fig. 4 shows a graph of a ratio of the
20 etching rate toward the $\langle 0-11 \rangle$ direction to the etching rate toward the $\langle 100 \rangle$ direction to against a ratio of concentration X of acetic acid to hydrochloric acid in the etchant. In Fig. 4, the ratio of concentration of hydrochloric acid: acetic
25 acid: water of the above-mentioned etchant is expressed by 1:X:1.

Referring to Fig. 4, it can be seen that the etching rate to the $\langle 0-11 \rangle$ direction is 30 to 160 times greater than the etching rate to the $\langle 100 \rangle$
30 direction for any concentration within the entire range of the acetic acid concentration X. Such an anisotropy of etching is obtained by hydrochloric acid and acetic acid contained in the etchant. Notably, it can be seen that a ratio of etching
35 rates which is greater than or equal to 30 is obtained when the ratio of concentration of acetic acid to hydrochloric acid to X is in the range

between 1 and 20. Accordingly, when the concentration of acetic acid in the etchant is chosen to be in the above-mentioned range, an object of the present invention to obtain a remarkable planarizing effect of the InP layer is achieved.

When the concentration ratio of the water in the above-mentioned etchant changes, the concentration of (hydrochloric acid + acetic acid) will change. Therefore, the absolute value of the etching rate will change, but anisotropy of etching shown in Figs. 3 and 4 will not change and therefore does not affect the planarizing effect.

Anisotropy of etching provided by the etchant of the present invention can also be obtained by adding hydrogen peroxide solution to the above-mentioned etchant mixture.

Fig. 5 is graph showing a ratio of etching rate toward the $\langle 0-11 \rangle$ direction to etching rate toward the $\langle 100 \rangle$ direction when a stepped configuration of InP is etched by an etchant obtained by adding hydrogen peroxide solution to the above-mentioned mixture containing hydrochloric acid, acetic acid and water.

Referring to Fig. 5, it can be seen that, when the composition ratio of hydrochloric acid, acetic acid, hydrogen peroxide solution and water in the above-mentioned etchant is expressed by 1:1:Y:1, an anisotropy of a value greater than or equal to 30 is obtained when the value of concentration Y of hydrogen peroxide solution is in a range between 0 to 0.3.

Fig. 6 is a graph showing an etching rate toward the $\langle 100 \rangle$ direction when the InP layer, an InGaAs layer and an InGaAsP layer having a composition giving a bandgap wavelength of $1.3 \mu\text{m}$ are wet-etched by an etchant containing hydrochloric acid, acetic acid, hydrogen peroxide solution and

water.

Referring to Fig. 6, it can be seen that the etching rate varies for each compound semiconductor layer depending of the composition of the etchant, particularly the concentration Y of hydrogen peroxide solution. It can be seen that the etching rate of the InP layer is not significantly changed by the concentration of the hydrogen peroxide solution in the above-mentioned etchant. However, there are significant changes in the etching rates of the InGaAs layer and the InGaAsP layer, and thus it can be seen that the etching rates for those III-V group layers significantly increase due to an increase of the concentration of hydrogen peroxide solution. For example, when the concentration of hydrogen peroxide solution Y in the etchant is less than 0.4 ($Y < 0.4$), the etching rate of the InP layer is greater than the etching rate of the InGaAsP layer. When the concentration of hydrogen peroxide solution Y in the etchant is greater than 0.4 ($Y > 0.4$), the relationship becomes opposite and the etching rate of the InGaAsP layer becomes greater than the etching rate of the InP layer. When the concentration of hydrogen peroxide solution Y in the etchant is set at a value equal to 0.4, the etching rate of the InGaAsP layer can be substantially matched with the etching rate of the InP layer.

Similarly, when the concentration of hydrogen peroxide solution Y in the etchant is less than 0.2 ($Y < 0.2$), the etching rate of the InP layer is greater than the etching rate of the InGaAs layer and when the concentration of hydrogen peroxide solution Y in the etchant is greater than 0.2 ($Y > 0.2$), the etching rate of the InGaAs layer is greater than the etching rate of the InP layer. Also, when the concentration of hydrogen peroxide

solution Y in the etchant is set at a value equal to 0.2, the etching rate of the InGaAs layer can be substantially matched with the etching rate of the InP layer.

5 The principle of the process of manufacturing the semiconductor device of the present invention will be described by categorizing the principle into four basic types.

A. TYPE I

10 Figs. 7A to 7D are diagrams showing a first type of the principle of the process of manufacturing the semiconductor device of the present invention based on the relationships shown in Figs. 3 to 6. In Figs. 7A to 7D, elements which
15 have been described above are denoted by similar reference numerals and will not be described in detail.

 Referring to Fig. 7A, in a manner similar to the structure shown in Fig. 1C, a mesa-stripe
20 structure is formed on the n-type InP substrate 11 by a dry-etching process using a mask which is an insulating film pattern of a material such as SiO₂ or SiN. The mesa-stripe structure includes the active layer 12 having a multi-quantum well
25 structure in which an InGaAsP quantum well layer and an InGaAsP barrier layer are alternately stacked, the p-type InP cladding layer 13 and the p-type InGaAs contact layer 14. However, the structure of Fig. 7A differs from the structure of Fig. 1C in
30 that a sacrificial layer or an etching rate adjusting layer 14A is inserted between the contact layer 14 and the insulating film pattern 15. Fe-doped InP high-resistance buried layers 16A and 16B are formed on both sides of the mesa-stripe
35 structure by a selective growth process using the insulating film pattern 15 as a mask. The InP buried layers 16A and 16B are provided with stepped

configurations 16a and 16b, similar to those shown in Fig. 1C, which are characteristic features of the selective growth process using an insulating film as a mask.

5 Then, in a step shown in Fig. 7B, the insulating film pattern 15 is removed. In a step shown in Fig. 7C, the structure shown in Fig. 7B is wet-etched using an etchant containing hydrochloric acid, acetic acid and hydrogen peroxide solution.
10 Then, as has been described with reference to Fig. 3, the inclined surfaces toward the $\langle 0-11 \rangle$ direction of the InP buried layers 16A and 16B are preferentially etched. As a result, planarized surfaces 16c and 16d formed of the (100), (011) or (0-1-1) surface
15 develop on the InP layers 16A and 16B. As can be seen from Figs. 4 and 5, the planarizing operation of the stepped surfaces by anisotropic etching of the InP layer is most prominent when the mixture ratio of hydrochloric acid, acetic acid and hydrogen
20 peroxide solution in the etchant is selected in a range between 1:1:0 and 10:10:3. In other words, for the composition in the above-mentioned range of composition, the etchant shows anisotropy of a value greater than or equal to 30.

25 In the wet-etching step shown in Fig. 7C, the InGaAs etching rate adjusting layer 14A is also etched, so that the (100), (011) or (0-1-1) surface is developed in the same manner as the above-mentioned InP buried layers 16A and 16B. When an
30 etchant for planarizing the InP layers 16A and 16B contains hydrochloric acid, acetic acid and hydrogen peroxide solution and has a composition with concentration of hydrogen peroxide solution Y being greater than 0.2 ($Y > 0.2$), it can be seen from Fig. 6
35 that the etching rate of the planarizing surfaces 16c, 16d becomes smaller than the etching rate of the InGaAs etching rate adjusting layer 14A. As a

result, the InGaAs etching rate adjusting layer 14A forms a recessed part that is recessed with respect to the InP buried layers 16A and 16B.

In the present invention, in the step shown in Fig. 7D, a further wet-etching process on the structure of Fig. 7C using a different etchant containing hydrochloric acid, acetic acid and hydrogen peroxide solution and having a composition with concentration of hydrogen peroxide solution Y being less than 0.2 ($Y < 0.2$). Accordingly, the InP planarized surfaces 16c and 16d are etched at an etching rate greater than the etching rate of the etching rate adjusting layer 14A. Such wet-etching is continued until the etching rate adjusting layer 14A is etched and removed, so as to obtain a planarized structure in which the planarized surfaces 16c and 16d are flush with the surface of the InGaAs contact layer 14.

In the processes shown in Figs. 7A to 7D, the same principle applies for a case where an InGaAsP layer having a bandgap composition of $1.3 \mu\text{m}$ shown in Fig. 6 is used as the etching rate adjusting layer 14A. It can be seen that the concentration of hydrogen peroxide solution Y of the etchant used in the process of Fig. 7C should be selected as being greater than 0.4 ($Y > 0.4$) and the concentration of hydrogen peroxide solution Y of the etchant used in the process of Fig. 7D should be selected as being less than 0.4 ($Y < 0.4$).

Also, in the process shown in Fig. 7D, in order to achieve a structure in which the surface of the contact layer 14 is flush with the planarized surfaces 16c and 16d of the InP buried layers 16A and 16B, the durations of the wet-etching processes of Figs. 7C and 7D must be appropriately selected based on the etching rates of the etchants used in the respective wet-etching processes.

In detail, assuming that the stepped parts 16a, 16b shown in Fig. 7B have great anisotropy of etching and thus immediately planarized when the wet-etching process of Fig. 7C is started, a stepped part L_{step} formed between the surface of the etching rate adjusting layer 14A and the planarized surface 16c or 16d in the process shown in Fig. 7C can be given by an equation:

$$L_{step} = (V_2 - V_1) \times t_1,$$

where V_1 is the etching rate of the InP layer 16A or 16B in the process shown in Fig. 7C;

V_2 is the etching rate of the etching rate adjusting layer 14A in the process shown in Fig. 7C; and

t_1 is an etching time in the process shown in Fig. 7C.

It is noted that the stepped part L_{step} should disappear as a result of the wet-etching process shown in Fig. 7D. Thus, the following relationship must hold, which can be shown by an expression:

$$L_{step} = (V_2 - V_1) \times t_1 = (V_3 - V_4) \times t_2,$$

where, V_3 is the etching rate of the InP layer 16A or 16B in the wet-etching process shown in Fig. 7D;

V_4 is the etching rate of the etching rate adjusting layer 14A in the wet-etching process shown in Fig. 7D; and

t_2 is an etching time in the process shown

in Fig. 7D.

Now, it is approximated from the relationship shown in Fig. 6 that the etching rate V_3 of the InP buried layer 16A, 16B in the process shown in Fig. 7D is approximately equal to the etching rate V_1 of the InP buried layer 16A, 16B in the process shown in Fig. 7C ($V_1 \doteq V_3$). Then, the above-mentioned relationship can be rewritten as:

10

$$(V_2 - V_1) \times t_1 = (V_1 - V_4) \times t_2.$$

To completely remove the etching rate adjusting layer 14A in the process shown in Fig. 7D, assuming that the relationship $V_1 \doteq V_3$ holds, the thickness of the etching rate adjusting layer 14A may be selected at a value defined by an equation $V_1 \times (t_1 + t_2)$.

20

B. TYPE II

Figs. 8A to 8D are diagrams showing a second type of the principle of the process of manufacturing the semiconductor device of the present invention for a case where the etching rate of planarizing the InP buried layers 16A and 16B is greater than the etching rate of the etching rate adjusting layer 14A. In Figs. 8A to 8D, elements which have been described above are denoted by similar reference numerals and will not be described in detail.

30

Referring to Figs. 8A to 8D, the processes of Figs 8A and 8B are the same as the processes shown in Figs. 7A and 7B. That is to say, an InGaAs or InGaAsP etching rate adjusting layer 14A is formed on a p-type InGaAs contact layer 14, a mesa-stripe structure is formed on the InP substrate 11 using an insulating film pattern 15 as a mask, high-

35

resistance InP buried layers 16A and 16B are formed on both sides of the mesa-stripe structure using the same insulating film pattern 15 as a selective-growth mask and the insulating film pattern 15 is removed.

In the process shown in Fig. 8C, a wet etching process is performed on the structure of Fig. 8B using an etchant containing hydrochloric acid, acetic acid and hydrogen peroxide solution and having a composition with the concentration of hydrogen peroxide solution being such that the etching rate of the InP buried layers 16A, 16B is greater than the etching rate of the etching rate adjusting layer 14A. Thus, the stepped parts 16a and 16b of the InP buried layers 16A and 16B are etched and produce the planarized surfaces 16c and 16d. As a result of such wet-etching process, the etching rate adjusting layer 14A protrudes upwardly from the planarized surfaces 16c and 16d and thus forms a protruded structure.

Thus, the process shown in Fig. 8C is followed by the process shown in Fig. 8D. The etching rate adjusting layer 14A and the InP planarized surfaces 16c, 16d are etched using an etchant containing hydrochloric acid, acetic acid and hydrogen peroxide solution and having a composition with the concentration of hydrogen peroxide solution being such that the etching rate of the etching rate adjusting layer is greater than the etching rate of InP.

For the processes shown in Figs. 8A to 8D, when the etching rate adjusting layer 14A is of InGaAs, in accordance with the relationship shown in Fig. 6, the concentration of hydrogen peroxide solution Y may be selected at a value less than 0.2 ($Y < 0.2$) for the process shown in Fig. 8C and at a value greater than 0.2 ($Y > 0.2$) for the process shown

in Fig. 8D. When the etching rate adjusting layer 14A is of InGaAsP layer which has a composition corresponding to a bandgap wavelength of a $1.3 \mu\text{m}$, the concentration of hydrogen peroxide solution Y may be selected at a value less than 0.4 ($Y < 0.4$) for the process shown in Fig. 8C and at a value greater than 0.4 ($Y > 0.4$) for the process shown in Fig. 8D.

Also, in the process shown in Fig. 8D, in order to achieve a structure in which the surface of the contact layer 14 is flush with the planarized surfaces 16c and 16d of the InP buried layers 16A and 16B, the durations of the wet-etching processes of Figs. 8C and 8D must be appropriately selected based on the etching rates of the etchants used in the respective wet-etching processes.

In detail, a stepped part L_{step} formed between the surface of the etching rate adjusting layer 14A and the planarized surface 16c or 16d in the step shown in Fig. 8C can be given by an equation:

$$L_{\text{step}} = (V_1 - V_2) \times t_1,$$

where V_1 is the etching rate of the InP layer 16A or 16B in the process shown in Fig. 8C; V_2 is the etching rate of the etching rate adjusting layer 14A in the process shown in Fig. 8C; and t_1 is an etching time in the process shown in Fig. 8C.

It is noted that the stepped part L_{step} should disappear as a result of the wet-etching process shown in Fig. 8D. Thus, the following relationship must hold, which can be shown by an expression:

$$L_{step} = (V_1 - V_2) \times t_1 = (V_4 - V_3) \times t_2,$$

5

where,

V_3 is the etching rate of the InP layer 16A or 16B in the wet-etching process shown in Fig. 8D;

10 V_4 is the etching rate of the etching rate adjusting layer 14A in the wet-etching process shown in Fig. 8D; and

t_2 is an etching time in the process shown in Fig. 8D.

15 It is approximated from the relationship shown in Fig. 6 that the etching rate V_3 of the InP buried layer 16A, 16B in the process shown in Fig. 8D is approximately equal to the etching rate V_1 of the InP buried layer 16A, 16B in the process shown
20 in Fig. 8C ($V_1 \doteq V_3$). Then, the above-mentioned relationship can be rewritten, in a similar manner to the case shown in Figs. 7C and 7D, as:

25 $(V_1 - V_2) \times t_1 = (V_4 - V_1) \times t_2.$

To completely remove the etching rate adjusting layer 14A in the process shown in Fig. 8D, assuming
30 that the relationship $V_1 \doteq V_3$ holds, the thickness of the etching rate adjusting layer 14A may be selected at a value defined by an equation $V_1 \times (t_1 + t_2)$.

C. TYPE III

35 Figs. 9A to 9C are diagrams showing a third type of the principle of the process of manufacturing the semiconductor device of the

present invention for a case where the etching rate of planarizing the InP buried layers 16A and 16B is equal to the etching rate of the etching rate adjusting layer 14A. In Figs. 9A to 9C, elements
5 which have been described above are denoted by similar reference numerals and will not be described in detail.

Referring to Figs. 9A to 9C, the processes of Figs 9A and 9B are the same as the processes
10 shown in Figs. 7A and 7B. That is to say, an InGaAs or InGaAsP etching rate adjusting layer 14A is formed on a p-type InGaAs contact layer 14, a mesa-stripe structure is formed on the InP substrate 11 using an insulating film pattern 15 as a mask, high-
15 resistance InP buried layers 16A and 16B are formed on both sides of the mesa-stripe structure using the same insulating film pattern 15 as a selective-growth mask and the insulating film pattern 15 is removed.

20 In the process shown in Fig. 9C, a wet etching process is performed on the structure of Fig. 9B using an etchant containing hydrochloric acid, acetic acid and hydrogen peroxide solution and having a composition with the concentration of
25 hydrogen peroxide solution being such that the etching rate of the InP buried layers 16A, 16B is approximately equal to the etching rate of the etching rate adjusting layer 14A. Thus, the stepped parts 16a and 16b of the InP buried layers 16A and
30 16B are etched and produce the planarized surfaces 16c and 16d. As a result of such wet-etching process, the etching rate adjusting layer 14A is etched at a rate that is substantially the same as that of the planarized surfaces 16c, 16d.
35 Accordingly, a single wet-etching process produces a planar structure in which the planarized surfaces 16c, 16d and the surface of the etching rate

adjusting layer 14A are substantially flush with each other.

For the processes shown in Figs. 9A to 9C, when the etching rate adjusting layer 14A is of InGaAs, in accordance with the relationship shown in Fig. 6, the concentration of hydrogen peroxide solution Y may be selected at a value approximately equal to 0.2 ($Y \approx 0.2$) for the process shown in Fig. 9C. When the etching rate adjusting layer 14A is of InGaAsP layer which has a composition corresponding to a bandgap wavelength of a 1.3 μm , the concentration of hydrogen peroxide solution Y may be selected at a value approximately equal to 0.4 ($Y \approx 0.4$) for the process shown in Fig. 9C.

For the process of manufacturing the semiconductor device in accordance with Type III illustrated in Figs. 9A to 9C, InP may be used as the etching rate adjusting layer 14A. When InP is used, in the wet-etching and planarizing process of Fig. 9C, there is no difference in the etching rates of the InP buried layer 16A, 16B and the etching rate adjusting layer 14A. Therefore, hydrogen peroxide solution contained in the etchant may be of any concentration.

25 D. TYPE IV

Figs. 10A to 10D are diagrams showing a fourth type of the principle of the process of manufacturing the semiconductor device of the present invention in which, when planarizing the InP buried layers 16A and 16B, the selective-growth mask used for forming the InP buried layer by a regrowth process is not removed and used as an etching mask. In Figs. 10A to 10D, elements which have been described above are denoted by similar reference numerals and will not be described in detail.

Referring to Figs. 10A to 10D, the process of Fig. 10A is the same as the process shown in Fig.

7A. That is to say, an InGaAs or InGaAsP etching rate adjusting layer 14A is formed on a p-type InGaAs contact layer 14, a mesa-stripe structure is formed on the InP substrate 11 using an insulating film pattern 15 as a mask, high-resistance InP buried layers 16A and 16B are formed on both sides of the mesa-stripe structure using the same insulating film pattern 15 as a selective-growth mask.

Then, in the process shown in Fig. 10B, with the insulating film pattern 15 being remained, a wet etching process is performed on the structure of Fig. 10A using an etchant containing hydrochloric acid, acetic acid and hydrogen peroxide solution. Thus, the stepped parts 16a and 16b of the InP buried layers 16A and 16B are etched and produce the planarized surfaces 16c and 16d. As a result of such wet-etching process, since the mesa-structure is protected by the insulating film pattern 15, the etching rate adjusting layer 14A protrudes upwardly from the planarized surfaces 16c and 16d and thus forms a protruded structure.

Then, in the process shown in Fig. 10C, the insulating film pattern 15 is removed. Further, in the process shown in Fig. 10D, the etching rate adjusting layer 14A and the InP planarized surfaces 16c and 16d are etched using an etchant containing hydrochloric acid, acetic acid and hydrogen peroxide solution and has a composition with concentration of hydrogen peroxide solution being selected such that the etching rate of the etching rate adjusting layer is greater than the etching rate of InP.

For the processes shown in Fig. 10B, when the etching rate adjusting layer 14A is of InGaAs, the concentration of hydrogen peroxide solution Y may be selected as any value on a graph of Fig. 5 within a range where surface orientation selectivity

is obtained. However, for the process shown in Fig. 10D, the concentration of hydrogen peroxide solution Y is preferably selected at a value greater than 0.2 ($Y > 0.2$) such that the etching rate adjusting layer 14A will be etched at a greater rate. When the etching rate adjusting layer 14A is of InGaAsP layer which has a composition corresponding to a bandgap wavelength of a $1.3 \mu\text{m}$, for the process shown in Fig. 10B, the concentration of hydrogen peroxide solution Y may be similarly selected as any value within a range where surface orientation selectivity is obtained. However, for the process shown in Fig. 10D, the concentration of hydrogen peroxide solution Y is preferably selected at a value greater than 0.4 ($Y > 0.4$) such that the InGaAsP etching rate adjusting layer 14A will be etched at a greater rate.

Also, in the process shown in Fig. 10D, in order to achieve a structure in which the surface of the contact layer 14 is flush with the planarized surfaces 16c and 16d of the InP buried layers 16A and 16B, the durations of the wet-etching processes of Figs. 10B and 10D must be appropriately selected based on the etching rates of the etchants used in the respective wet-etching processes.

In detail, a stepped part L_{step} formed between the surface of the etching rate adjusting layer 14A and the planarized surface 16c or 16d in the step shown in Fig. 10B can be given by an equation:

30

$$L_{\text{step}} = V_1 \times t_1,$$

35 where V_1 is the etching rate of the InP layer 16A or 16B in the process shown in Fig. 10B; and

t_1 is an etching time in the process shown in Fig. 10B.

It is noted that the stepped part L_{step} should disappear as a result of the wet-etching process shown in Fig. 10D. Thus, the following relationship must hold, which can be shown by an expression:

10
$$L_{step} = V_1 \times t_1 = (V_4 - V_3) \times t_2,$$

where,

V_3 is the etching rate of the InP layer 15 16A or 16B in the wet-etching process shown in Fig. 10D;

V_4 is the etching rate of the etching rate adjusting layer 14A in the wet-etching process shown in Fig. 10D; and

20 t_2 is an etching time in the process shown in Fig. 10D.

Now, it is approximated from the relationship shown in Fig. 6 that the etching rate V_3 of the InP buried layer 16A, 16B in the process shown in Fig. 10D is approximately equal to the 25 etching rate V_1 of the InP buried layer 16A, 16B in the process shown in Fig. 10B ($V_1 \doteq V_3$). Then, the above-mentioned relationship can be rewritten as:

30

$$V_1 \times t_1 = (V_4 - V_1) \times t_2.$$

To completely remove the etching rate adjusting 35 layer 14A in the process shown in Fig. 10D, assuming that the relationship $V_1 \doteq V_3$ holds, the thickness of the etching rate adjusting layer 14A may be

selected at a value d defined by an equation $V_1 \times (t_1 + t_2)$.

For the above-described types I to IV, InGaAs or InGaAsP or InP is used as the etching rate adjusting layer 14A. However, the material of the etching rate adjusting layer 14A is not limited to such material, but may also be any one of InGaAs, InAs, InGaP, InGaAsP and GaInNAs. In order to vary the selectivity of etching between the wet-etching process and the planarizing process, the concentration of acetic acid X in the etchant may be altered. Particularly when the etching rate adjusting layer 14A is of InGaAsP with the composition having a bandgap within a range between 1.3 μm and 1.65 μm , a value between the etching rate of InGaAsP and the etching rate of InGaAs for the 1.3 μm composition is obtained in accordance with the relationship shown in Fig. 6.

In the principle described above, the stepped part between the embedded InP layer 16A, 16B and the contact layer 14 are substantially eliminated by performing one or two wet-etching and planarizing process/processes. However, the present invention not only includes a case where the stepped part is completely eliminated but also a case where the stepped part has been reduced compared to the original state as a result of the planarizing process.

Also, regarding the process of planarizing the original stepped parts 16a and 16b on the InP buried layers 16A and 16B based on the relationships illustrated in Figs. 3 to 5, such as the process shown in Fig. 7C, the present invention includes not only a case where the planarized surfaces 16c and 16d obtained as a result of wet-etching is flush with the (100), (011) and (0-1-1) surface but also a case where a surface having an index closer to those

crystal surfaces is obtained.

Referring now to Figs. 11A to 12G, a process of manufacturing a laser diode having a BH structure of a first embodiment of the present invention will be described.

As shown in Fig. 11A, on an n-type InP substrate 101, an InGaAsP/InGaAsP multi-quantum well active layer 102, a p-type InP cladding layer 103, and a p-type InGaAs contact layer 104 are successively stacked and then an etching rate adjusting layer 104A of InGaAsP having a composition giving a bandgap wavelength of $1.3 \mu\text{m}$ is stacked with a thickness of about $0.4 \mu\text{m}$.

Then, in a process shown in Fig. 11B, dry-etching is performed using the SiO_2 film 105 as an etching mask so as to form an active layer mesa-stripe 101M. In the illustrated example, the active layer mesa-stripe 101M extend in the $\langle 011 \rangle$ direction.

Then, in a process shown in Fig. 11C, a MOVPE method is implemented using the SiO_2 film 105 as a selective growth mask. Thus, Fe-doped InP buried layers 106₁, 106₂ are formed on the substrate 101 on both sides of the mesa-stripe 101M. The above-described MOVPE method is performed under a condition of, for example, a growth temperature of 630°C and a growth pressure of 0.1 atmosphere. TMIn, PH_3 and Cp_2Fe are used as materials of III group element, V group element and Fe-dopants, respectively.

In the present embodiment, the thickness of the InP buried layer 106₁, 106₂ are chosen such that the lowermost part of the InP buried layer 106₁, 106₂ is at a level higher than the InGaAsP etching rate adjusting layer 104A in the mesa-stripe 101M. As a result of the process shown in Fig. 11C, raised parts 106a, 106b are formed on the InP buried layer 106₁, 106₂, respectively, at positions adjacent the

SiO₂ film 105 on the mesa-stripe 101M.

In a process shown in Fig. 12D, the structure shown in Fig. 11C is wet-etched using a first etchant which is a mixture of hydrochloric acid, acetic acid, hydrogen peroxide solution and water.

In the process shown in Fig. 12D, the composition ratio of hydrochloric acid, acetic acid, hydrogen peroxide solution and water in the above-mentioned etchant is selected as 1:1:0.1:1. The etching process is performed with a temperature of the mixture at 23°C and typically for 1 minute. As a result of such an etching process, as shown in Fig. 12D, the surfaces 106a, 106b of the InP buried layers 106₁, 106₂ changes to the (100) surfaces or planarized surfaces 106c, 106d near the (100) surfaces. The planarized surfaces 106c, 106d form stepped parts having a height of about 0.12 μm with respect to the surface of the InGaAsP layer 104A protected by the SiO₂ film 105.

Then, in a process shown in Fig. 12E, the SiO₂ film 105 is removed by an HF treatment. Then in a process shown in Fig. 12F, the structure shown in Fig. 12E is wet-etched using a second etchant which is a mixture of hydrochloric acid, acetic acid, hydrogen peroxide solution and water until the p-type InGaAs contact layer 104 underlying the InGaAsP layer 104A is exposed.

In the wet-etching process shown in Fig. 12F, the composition ratio of hydrochloric acid, acetic acid, hydrogen peroxide solution and water is selected as 1:1:0.6:1. The etching process is performed with a temperature of the mixture at 23°C and typically for 2 minutes. In the wet-etching process using the second etchant, the etching rate of the InGaAsP layer 14A becomes greater than the etching rate of the InP buried layers 106₁, 106₂.

As a result, the stepped part on the surface produced in the process shown in Fig. 12E disappears. Accordingly, as shown in Fig. 12F, the InP buried layers 106₁, 106₂ and the contact layer 104 become flush.

Finally, a process shown in Fig. 12G, a p-side electrode 107 is formed on the p-type InGaAs layer 104 and an n-side electrode 108 is formed on a lower surface of the substrate 101.

In the present embodiment, the InP buried layers 106₁, 106₂ is flush with the contact layer 104. Therefore, the p-side electrode 107 is stacked on a flat surface and thus the break of the electrode illustrated in Fig. 2 will not occur.

Referring now to Figs. 13A to 14F, a process of manufacturing a laser diode having a BH structure of a second embodiment of the present invention will be described. In Figs. 13A to 14F, elements which have been described above are denoted by similar reference numerals and will not be described in detail.

Referring to Figs. 13A to 14F, processes shown in Figs. 13A to 13C are substantially the same as the processes shown in Figs. 11A to 11C. That is to say, InP buried layers 106₁ and 106₂ are formed by a regrowth process using the SiO₂ film 105 as a selective growth mask on both sides of the mesa-structure 101M covered by SiO₂ film 105. During the regrowth process, the stepped parts 106a and 106b are formed on the InP buried layers 106₁ and 106₂, respectively. In the processes shown in Figs. 13A to 13C, the InGaAsP layer 104A having a composition giving a bandgap wavelength of 1.3 μ m are formed with a thickness of about 0.52 μ m.

Then in the process of Fig. 14D, the SiO₂ film 105 is removed by an HF treatment. Then in a process shown in Fig. 14E, the structure shown in

Fig. 14D is wet-etched using a first etchant which is a mixture of hydrochloric acid, acetic acid, hydrogen peroxide solution and water.

In the process shown in Fig. 14E, the composition ratio of hydrochloric acid, acetic acid, hydrogen peroxide solution and water in the above-mentioned etchant is selected as 1:1:0.1:1. The etching process is performed with a temperature of the mixture at 23°C and typically for 1 minute. When the first etchant is used, the etching rate of the InP buried layer 106₁ and 106₂ is greater than the etching rate of the InGaAsP etching rate adjusting layer 104A. As a result of such an etching process, as shown in Fig. 14E, the surfaces 106a, 106b of the InP buried layers 106₁, 106₂ changes to the (100) surfaces or planarized surfaces 106c, 106d near the (100) surfaces. Thus-formed planarized surfaces 106c, 106d form steps having a height of about 0.12 μm with respect to the surface of the InGaAsP layer 104A. Thus, a protruded structure having a height 0.12 μm is formed on the structure shown in Fig. 14E.

Then, in a process shown in Fig. 14F, the structure shown in Fig. 14E is wet-etched using a second etchant which is a mixture of hydrochloric acid, acetic acid, hydrogen peroxide solution and water until the p-type InGaAs contact layer 104 underlying the InGaAsP layer 104A is exposed.

In the wet-etching process shown in Fig. 14F, the composition ratio of hydrochloric acid, acetic acid, hydrogen peroxide solution and water is selected as 1:1:0.6:1. The etching process is performed with a temperature of the mixture at 23°C and typically for 2 minutes. In the wet-etching process using the second etchant, the etching rate of the InGaAsP etching rate adjusting layer 14A becomes greater than the etching rate of the InP

buried layers 106₁, 106₂. As a result, the stepped part of the surface produced in the process shown in Fig. 14E disappears. Accordingly, as shown in Fig. 14F, the InP buried layers 106₁, 106₂ and the
5 contact layer 104 become flush.

Finally, although not shown in the figures, in a manner similar to a process shown in Fig. 12G, a p-side electrode 107 is formed on the p-type InGaAs layer 104 and an n-side electrode 108 is
10 formed on a lower surface of the substrate 101.

In the present embodiment, the embedded layers 106₁, 106₂ form a planarized surface with the contact layer 104. Therefore, the p-side electrode 107 is stacked on a flat surface and thus the break
15 of the electrode illustrated in Fig. 2 will not occur.

Referring now to Figs. 15A to 16F, a process of manufacturing a laser diode having a BH structure of a third embodiment of the present
20 invention will be described. In Figs. 15A to 16F, elements which have been described above are denoted by similar reference numerals and will not be described in detail.

Referring to Figs. 15A to 16F, processes
25 shown in Figs. 15A to 15C are substantially the same as the processes shown in Figs. 13A to 13C. That is to say, InP buried layers 106₁ and 106₂ are formed by a regrowth process using the SiO₂ film 105 as a selective growth mask on both sides of the mesa-
30 structure 101M covered by SiO₂ film 105. During the regrowth process, the stepped parts 106a and 106b are formed on the InP buried layers 106₁ and 106₂, respectively. In the processes shown in Figs. 15A to 15C, the InGaAs layer 104A are formed with a
35 thickness of about 0.52 μ m.

Then in the process of Fig. 16D, the SiO₂ film 105 is removed by an HF treatment. Then in a

process shown in Fig. 16E, the structure shown in Fig. 16D is wet-etched using a first etchant which is a mixture of hydrochloric acid, acetic acid, hydrogen peroxide solution and water.

5 In the process shown in Fig. 16E, the composition ratio of hydrochloric acid, acetic acid, hydrogen peroxide solution and water in the above-mentioned etchant is selected as 1:1:0.3:1. The etching process is performed with a temperature of
10 the mixture at 23°C and typically for 1 minute. When the first etchant is used, the etching rate of the InP buried layer 106₁ and 106₂ is smaller than the etching rate of the InGaAs etching rate adjusting layer 104A. As a result of such an
15 etching process, as shown in Fig. 16E, the surfaces 106a, 106b of the InP buried layers 106₁, 106₂ changes to the (100) surfaces or planarized surfaces 106c, 106d near the (100) surfaces. Thus-formed planarized surfaces 106c, 106d form stepped parts
20 having a height of about 0.12 μm with respect to the surface of the InGaAs layer 104A. Thus, a recessed structure having a depth 0.12 μm is formed on the structure shown in Fig. 16E.

Then, in a process shown in Fig. 16F, the
25 structure shown in Fig. 16E is wet-etched using a second etchant which is a mixture of hydrochloric acid, acetic acid, hydrogen peroxide solution and water until the p-type InGaAs contact layer 104 underlying the InGaAs layer 104A is exposed.

30 In the wet-etching process shown in Fig. 16F, for the second etchant, the composition ratio of hydrochloric acid, acetic acid, hydrogen peroxide solution and water is selected as 1:1:0.1:1. The etching process is performed with a temperature of
35 the mixture at 23°C and typically for 2 minutes. In the wet-etching process using the second etchant, the etching rate of the InGaAs etching rate

adjusting layer 14A becomes smaller than the etching rate of the InP buried layers 106₁, 106₂. As a result, the stepped parts of the surface produced in the process shown in Fig. 16E disappears.

5 Accordingly, as shown in Fig. 16F, the InP buried layers 106₁, 106₂ and the contact layer 104 become flush.

10 Finally, although not shown in the figures, in a manner similar to a process shown in Fig. 12G, a p-side electrode 107 is formed on the p-type InGaAs layer 104 and an n-side electrode 108 is formed on a lower surface of the substrate 101.

15 In the present embodiment, the embedded layers 106₁, 106₂ form a planarized surface with the contact layer 104 in the step shown in Fig. 16F. Therefore, the p-side electrode 107 is stacked on a flat surface and thus the break of the electrode illustrated in Fig. 2 will not occur.

20 Referring now to Figs. 17A to 18E, a process of manufacturing a laser diode having a BH structure of a fourth embodiment of the present invention will be described. In Figs. 17A to 18E, elements which have been described above are denoted by similar reference numerals and will not be
25 described in detail.

Referring to Figs. 17A to 18E, processes shown in Figs. 17A to 18E are substantially the same as the processes shown in Figs. 13A to 13C. That is to say, InP buried layers 106₁ and 106₂ are formed
30 by a regrowth process using the SiO₂ film 105 as a selective growth mask on both sides of the mesa-structure 101M covered by SiO₂ film 105. During the regrowth process, the stepped parts 106a and 106b are formed on the InP buried layers 106₁ and 106₂,
35 respectively. In the processes shown in Figs. 17A to 17C, the InGaAs layer 104A are formed with a thickness of about 0.28 μ m.

Then in the process of Fig. 18D, the SiO_2 film 105 is removed by an HF treatment. Then in a process shown in Fig. 18E, the structure shown in Fig. 18D is wet-etched using an etchant which is a mixture of hydrochloric acid, acetic acid, hydrogen peroxide solution and water.

In the process shown in Fig. 18E, the composition ratio of hydrochloric acid, acetic acid, hydrogen peroxide solution and water in the above-mentioned etchant is selected as 1:1:0.2:1. The etching process is performed with a temperature of the mixture at 23°C and typically for 2 minutes. When the above-mentioned etchant is used, substantially the same etching rate is obtained for the InP buried layers 106₁ and 106₂ and for the InGaAs etching rate adjusting layer 104A. As a result of such an etching process, as shown in Fig. 18E, the surfaces 106a, 106b of the InP buried layers 106₁, 106₂ changes to the (100) surfaces or planarized surfaces 106c, 106d near the (100) surfaces and the planarized surfaces 106c and 106d form planarized surfaces which are substantially flush with the surface of the InGaAs contact layer 104.

Finally, although not shown in the figures, in a manner similar to a process shown in Fig. 12G, a p-side electrode 107 is formed on the p-type InGaAs layer 104 and an n-side electrode 108 is formed on a lower surface of the substrate 101.

In the present embodiment, the embedded layers 106₁, 106₂ form a planarized surface with the contact layer 104 in the step shown in Fig. 18E. Therefore, the p-side electrode 107 is stacked on a flat surface and thus the break of the electrode illustrated in Fig. 2 will not occur.

Referring now to Figs. 19A to 20E, a process of manufacturing a laser diode having a BH

structur of a third embodiment of the present invention will be described. In Figs. 19A to 20E, elements which have been described above are denoted by similar reference numerals and will not be described in detail.

Referring to Figs. 19A to 20E, processes shown in Figs. 19A to 20E are substantially the same as the processes shown in Figs. 13A to 13C. That is to say, InP buried layers 106₁ and 106₂ are formed by a regrowth process using the SiO₂ film 105 as a selective growth mask on both sides of the mesa-structure 101M covered by SiO₂ film 105. During the regrowth process, the stepped parts 106a and 106b are formed on the InP buried layers 106₁ and 106₂, respectively. In the processes shown in Figs. 19A to 19C, instead of the InGaAs layer 104A used in the processes of Figs. 13A to 13C, the InP layer 104B is formed on the contact layer 104 with a thickness of about 0.2 μ m.

Then in the process of Fig. 20D, the SiO₂ film 105 is removed by an HF treatment. Then in a process shown in Fig. 20E, the structure shown in Fig. 20D is wet-etched using an etchant which is a mixture of hydrochloric acid, acetic acid and water.

In the process shown in Fig. 20E, the composition ratio of hydrochloric acid, acetic acid and water in the above-mentioned etchant is selected as 1:5:1. The etching process is performed with a temperature of the mixture at 23°C and typically for 2 minutes. As a result of such an etching process, as shown in Fig. 20E, the surfaces 106a, 106b of the InP buried layers 106A, 106B changes to the (100) surfaces or planarized surfaces 106c, 106d near the (100) surfaces and the planarized surfaces 106c and 106d form planarized surfaces which are substantially flush with the surface of the InGaAs contact layer 104.

Finally, although not shown in the figures,
in a manner similar to a process shown in Fig. 12G,
a p-side electrode 107 is formed on the p-type
InGaAs layer 104 and an n-side electrode 108 is
5 formed on a lower surface of the substrate 101.

In the present embodiment, the embedded
layers 106₁, 106₂ form a planarized surface with the
contact layer 104 in the step shown in Fig. 20E.
Therefore, the p-side electrode 107 is stacked on a
10 flat surface and thus the break of the electrode
illustrated in Fig. 2 will not occur.

Further, the present invention is not
limited to these embodiments, and variations and
modifications may be made without departing from the
15 scope of the present invention.

The present application is based on
Japanese priority application No. 2001-039252 filed
on February 15, 2001, the entire contents of which
are hereby incorporated by reference.
20